



Sierraform® GT

CalMag

For soil low in calcium and magnesium

14 | 0 | 7 | 8 | 5 | TE
N | P2O5 | K2O | CaO | MgO



Guaranteed analysis

oxide		
N	Total Nitrogen	14%
	Nitrate nitrogen (N-NO3)	0%
	Ammoniacal nitrogen (N-NH4)	1.3%
	Urea nitrogen (N-Urea)	2.9%
	Organic nitrogen	0%
P2O5	Phosphorus Pentoxide	0%
	Water soluble (P2O5)	0%
K2O	Potassium Oxide	7%
	Water Soluble (K2O)	7%
CaO	Calcium Oxide	8%
	Water soluble (CaO)	8%
MgO	Magnesium Oxide	5%
	Water soluble (MgO)	5.0%
Cu	Copper	0.02%
	Water soluble (Cu)	0%
	Copper EDTA (Cu)	0%
Fe	Iron	0.5%
	Water soluble (Fe)	0%
	Iron EDTA (Fe)	0%
	Iron DTPA (Fe)	0%
	Iron EDDHA (Fe)	0%
Mn	Manganese	0.100%
	Water soluble (Mn)	0%
	Manganese EDTA (Mn)	0%
Mo	Molybdenum	0.001%
	Water soluble (Mo)	0%
Zn	Zinc	0.02%
	Water soluble (Zn)	0%
	Zinc EDTA (Zn)	0%

Description

Just what your turf's crying out for. This one is perfect if your soil needs extra calcium and magnesium. As well as these, it also contains trace elements, SeaMax for improved stress tolerance and stronger roots, and sustained-release MU-based nitrogen for regular, steady growth. You'll get even coverage with these compound mini granules, and you don't need to use huge amounts. No phosphates, so no phosphor build-up. Ideal throughout the summer on all fine turf. Healthier grass all round, with nutrients released for up to 8 – 10 weeks.

Benefits

- \\ Extra calcium and magnesium, plus trace elements
- \\ MU formula: nitrogen released slowly
- \\ Stronger roots, healthier grass, steady growth

How to use

- 1 Apply to dry foliage and irrigate after 1 – 2 days if there is no rainfall.
- 2 Irrigation helps with dispersion and lowers risk of mower pick-up on close cut surfaces.
- 3 Watering-in after application will minimize footprint trails. Avoid applying during frosty or drought conditions.
- 4 Delay any vertical cutting and/or grooming until 3 days after application, to allow the granules to properly disperse. Significantly less nitrogen is released when soil temperatures are below 10° C.
- 5 If spilled on pavement, concrete, clothes, etc. brush off immediately as it can stain. Contains iron: do not apply in case of risk of contact with concrete, marble, stone, fabric, or swimming pools.
- 6 If you need more information, please contact your technical support.

Application rates

Recommended Rate:

15 – 30 g/m²

Trail first on a small scale before changing the rate, or any other variables, As circumstances can differ and the application of our products is beyond our control, ICL cannot be held responsible for any adverse results.

Attention

Trial first on a small scale before changing the rate, application, or any other variables. As circumstances can differ and as the application of our products is beyond our control, ICL cannot be held responsible for any adverse results. Contact your ICL advisor for more detailed advice.
